

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1. *(Original)* A mechanic's creeper, comprising:

a hollow tubular main frame having at least a left side member, a right side member, and a head crossmember;

a frame extension having at least a left side member, a right side member, and a foot crossmember, with the left side member and the right side member of said frame extension telescopingly disposed respectively within the left side member and the right side member of said main frame;

a back rest pad secured to said main frame;

a buttocks support cushion removably attached to said frame extension;

a left and a right head end wheel depending from said main frame, near said head crossmember thereof; and

a left and a right foot end wheel depending from said frame extension adjacent said foot crossmember thereof.

Claim 2. *(Original)* The mechanic's creeper according to claim 1, further including a tool and equipment storage compartment disposed between said left side member and said right side member of said main frame, and below said back rest pad.

Claim 3. *(Original)* The mechanic's creeper according to claim 1, further including a storage and carrying case therefor.

Claim 4. *(Original)* The mechanic's creeper according to claim 1, further including a left and a right arm rest removably attached respectively to said left side member and said right side member of said main frame.

Claim 5. *(Original)* The mechanic's creeper according to claim 4, further including a tool storage pouch foldably depending from each said arm rest.

Claim 6. *(Original)* The mechanic's creeper according to claim 1, further including at least one adjustably positionable work light extending from said main frame adjacent said head crossmember thereof.

Claim 7. *(Original)* The mechanic's creeper according to claim 1, further including a warning light removably attached to said main frame.

Claim 8. (Original) A mechanic's creeper, comprising:

a hollow tubular frame assembly having at least a left side member, a right side member, a head crossmember, and a foot crossmember;

a tool and equipment storage compartment disposed between the left side member and the right side member of said frame assembly;

a back rest pad hingedly secured to one of the side members of said frame assembly and over said tool and equipment storage compartment; and

a left and a right head end wheel, and a left and a right foot end wheel, the wheels depending from said frame assembly.

Claim 9. (Original) The mechanic's creeper according to claim 8, wherein said frame assembly comprises:

a hollow tubular main frame having at least a left side member, a right side member, and a head crossmember;

a frame extension having at least a left side member, a right side member, and a foot crossmember, with the left side member and the right side member of said frame extension telescopingly disposed respectively within the left side member and the right side member of said main frame; and

a buttocks support cushion removably attached to said frame extension.

Claim 10. *(Original)* The mechanic's creeper according to claim 8, further including a storage and carrying case therefor.

Claim 11. *(Original)* The mechanic's creeper according to claim 8, further including a left and a right arm rest removably attached respectively to said left side member and said right side member of said frame assembly.

Claim 12. *(Original)* The mechanic's creeper according to claim 11, further including a tool storage pouch foldably depending from each said arm rest.

Claim 13. *(Original)* The mechanic's creeper according to claim 8, further including at least one adjustably positionable work light extending from said frame assembly adjacent said head crossmember thereof.

Claim 14. *(Original)* The mechanic's creeper according to claim 8, further including a warning light removably attached to said frame assembly.

Claim 15. *(Currently Amended)* A mechanic's creeper, comprising:

a hollow tubular frame assembly having at least a left side member, a right side member, a head crossmember, and a foot crossmember;

a back rest pad secured to said main frame;

a left and a right head end wheel, and a left and a right foot end wheel, the wheels depending from said frame assembly; [[and]]

a hollow tubular main frame having at least a left side member, a right side member, and a head crossmember;

a frame extension having at least a left side member, a right side member, and a foot crossmember, with the left side member and the right side member of said frame extension telescopingly disposed respectively within the left side member and the right side member of said main frame;

a buttocks support cushion removably attached to said frame extension; and

a storage and carrying case configured for storing and carrying therein, at least said frame assembly including said back rest pad and each said wheel.

Claim 16. *(Cancelled)*

Claim 17. *(Original)* The mechanic's creeper according to claim 15, further including a tool and equipment storage compartment disposed between said left side member and said right side member of said frame assembly, and below said back rest pad.

Claim 18. *(Cancelled)*

Claim 19. *(Currently Amended)* A mechanic's creeper, comprising:

a hollow tubular frame assembly having at least a left side member, a right side member, a head crossmember, and a foot crossmember;

a back rest pad secured to said main frame;

a left and a right head end wheel, and a left and a right foot end wheel, the wheels depending from said frame assembly;

a left and a right arm rest removably attached respectively to said left side member and said right side member of said frame assembly;

~~The mechanic's creeper according to claim 18, further including a tool storage pouch foldably depending from each said arm rest; and~~

a storage and carrying case configured for storing and carrying therein, at least said frame assembly including said back rest pad and each said wheel.

Claim 20. *(Original)* The mechanic's creeper according to claim 15, further including:

at least one adjustably positionable work light extending from said frame assembly adjacent said head crossmember thereof; and

a warning light removably attached to said frame assembly.